

WIRE ROPE SPELTER SOCKET

WIRE ROPE SPELTER SOCKET – CLOSED TYPE

Product Code: CA-0101

Nominal Size of Rope		Dimension (mm)								Weight (kgs)
(mm)	(Inch)	A	B	C	D	E	F	G	H	
16 – 20	$\frac{5}{8} - \frac{13}{16}$	213	92	82	49	36	24	33	27	3
22 – 26	$\frac{7}{8} - 1$	260	112	103	62	47	31	42	33	5
28 – 32	$1\frac{1}{8} - 1\frac{1}{4}$	309	132	124	75	57	38	52	40	11.3
34 – 38	$1\frac{5}{16} - 1\frac{1}{2}$	354	152	145	80	66	44	62	47	13.5
40 – 42	$1\frac{9}{16} - 1\frac{5}{8}$	384	165	146	83	76	48	70	54	17
44 – 48	$1\frac{3}{4} - 1\frac{7}{8}$	439	192	171	90	80	52	76	56	26
50 – 54	$2 - 2\frac{1}{8}$	495	217	194	96	97	60	83	62	40
56 – 60	$2\frac{1}{4} - 2\frac{3}{8}$	537	241	216	109	102	66	92	67	51
62 – 66	$2\frac{1}{2} - 2\frac{5}{8}$	597	270	241	140	114	76	102	79	64
70 – 74	$2\frac{3}{4} - 2\frac{7}{8}$	644	286	273	159	125	80	124	79	90
76 – 80	$3 - 3\frac{1}{8}$	687	299	292	171	133	86	133	83	110

- Remark: 1. Material : Cast Alloy Steel.
 2. Finishing : Blasting and Hot Dip Galvanized.
 3. 100% Proof Load (40% of MBL of Rope).
 4. Standard : comply with ISO 3189 requirement.
 5. Proved by Prototype Testing.
 6. Socketing Procedure as request.

Closed Type

